



HARM3002

Harmony 9W 410LM 3000K IP20 LED Up/Down WhiteWall Light



General Details

Finish	White Powder Coated Aluminium
Product Weight	1.0kg
Overall Dimensions	A 100mm X B 160mm x C 50mm
Bar Coding	Saturn LED coding in accordance with EAN-12 & ITF-14
IP Rating	IP20
Energy Rating	A* - (Very Low Energy)

Light Source

Wattage & Lumens	9W - 410LM - 46 lm/W
Colour Temperature	3000K
CRI Ra	Ra > 80
Lifespan	30,000 Hours
Lamp Working Temperature	<50°C
Beam Angle	60° Up/Down



Electrical

Voltage	220-240V. 50 / 60Hz. AC.
---------	--------------------------

Running Current (I)	0.06A
---------------------	-------

Total Running Wattage (W)	9W
---------------------------	----

Electrical Classification	Class I
---------------------------	---------

Power Factor Correction (PFC)	> 0.7
-------------------------------	-------

Cabling Electrical Connections	Screw fix in terminal block
--------------------------------	-----------------------------

LED Driver	Tridonic
------------	----------

Installation

Method of Fix	Surface mounted on a suitable substrate
---------------	---

Recommended Working Temperature	Minimum Temp -10°C to Maximum Temp + 40°C
---------------------------------	---

Instruction Sheet	Supplied with product
-------------------	-----------------------

Origin & Markets

Country of Manufacture	Designed & tested in Europe - Manufactured in China
------------------------	---

Intended Market	Europe, Middle East & Australia 220 - 240Volt
-----------------	---

Materials

Main Housing Material	Aluminium Body & Polycarbonate Diffuser
-----------------------	---

Fixings Main Housing	
----------------------	--

Front Shield	Clear Polycarbonate Diffuser
--------------	------------------------------

Approvals

Warranty	3 Year Warranty - For more information go to www.saturnled.eu/warranty
----------	---

Marks & Symbols	CE -- SELV -- RoHS -- EMC -- WEEE
-----------------	-----------------------------------

Quality Assurance System	SaturnLED quality assurance to ISO9001:2008
--------------------------	---

Manufactured in Accordance to	British Standard - BS EN 60598 - 2 - 1
-------------------------------	--

