



### **WARR1001**

Warrior 22W 1500LM Dual CCT IP65 Anthracite LED Wall Pack







#### **General Details**

Pludali	
Finish	Anthracite Polycarbonate Body & Polycarbonate Diffuser
Product Weight	1.6kg
Overall Dimensions	A 305mm X B 255mm x C 101mm
Bar Coding	Saturn LED coding in accordance with EAN-12 & ITF-14
IP Rating	IP65
Energy Rating	A* - (Very Low Energy)

## **Light Source**

Wattage & Lumens	22W -1500LM - 68 lm/W
Colour Temperature	3000K/4000K
CRI Ra	Ra > 80
Lifespan	50,000 Hours
Lamp Working Temperature	<50°C
Beam Angle	90°





#### **Electrical**

220-240V. 50 / 60Hz. AC.
110mA
22W
Class II
0.9
Screw fix in terminal block
Tridonic

### Installation

Method of Fix	Surface mounted on a suitable substrate.
Recommended Working Temperature	Minimum Temp -10°C to Maximum Temp + 40°C
Instruction Sheet	Supplied with product

# **Origin & Markets**

Country of Manufacture	Designed & tested in Europe - Manufactured in China
Intended Market	Europe, Middle East & Australia 220 - 240Volt

#### **Materials**

Main Housing Material	Polycarbonate
Fixings Main Housing	Zinc plated screws (Internal)
Front Shield	Polycarbonate Opal Diffuser

# **Approvals**

Warranty	5 Year Warranty - For more information go to www.saturnled.eu/warranty
Marks & Symbols	CE SELV RoHS EMC WEEE
Quality Assurance System	SaturnLED quality assurance to ISO9001:2008
Manufactured in Accordance to	British Standard - BS EN 60598 - 2 - 1



