

GLAD/1500/3300

Gladiator 33W 4000K IP65 1500mm Anti-Corrosion Luminaire



General Details

| | |
|---|--|
| Finish | Polycarbonate Base & Opal Diffuser c/w Stainless Steel Clips |
| Product Weight | 4.9kg |
| Overall Dimensions | 1500mm X 90mm X 100mm |
| Carton Weight / Material | 3.90 kg / Cardboard |
| Packaging & Labelling Guidelines | Saturn LED.eu - Generic labelling |
| Bar Coding | Saturn LED coding in accordance with EAN-12 & ITF-14 |
| IP Rating | IP65 |
| Energy Rating | A* - (Very Low Energy) |

Light Source

| | |
|------------------------------|---|
| Rated Wattage | 33W |
| Lumens | 3300 |
| Lumens Per Watt | 100 |
| Recommended Product Location | Exterior or Interior where IP Rating is Required |
| Light Source Brand | Epistar LED Chips |
| Colour Temperature | 4000K |
| CRI Ra | Ra > 80 |
| Lifespan | 50,000 Hours |
| Lamp Working Temperature | <50°C |
| Beam Angle | 140° |
| Photometric Data | Visit www.saturnled.eu for full Photometric files |
| Lamp Code | N/A |

Electrical

| | |
|--------------------------------|-------------------------------------|
| Voltage | 220-240V. 50 / 60Hz. AC. |
| Running Current (I) | 240mA |
| Total Running Wattage (W) | 52W |
| Electrical Classification | Class I |
| Power Factor Correction (PFC) | 0.9 |
| Cabling Electrical Connections | Screw fix in terminal block |
| LED Driver | Pri: 240V ac. Sec: 700mA Max DC 93V |

Installation

| | |
|---|---|
| Distance from Illuminated Object | 0.5m |
| Method of Fix | Wire Suspended / Surface Mount |
| Recommended Working Temperature | Minimum Temp -10°C to Maximum Temp + 40°C |
| Instruction Sheet | Supplied with product |

Origin & Markets

| | |
|-------------------------------|---|
| Country of Manufacture | Designed & tested in Europe - Manufactured in China |
| Intended Market | Europe, Middle East & Australia 220 - 240Volt |

Materials

| | |
|------------------------------|---------------------------------|
| Main Housing Material | |
| Fixings Main Housing | Stainless Steel Clips and Hooks |
| Front Shield | Polycarbonate Cover |

Approvals

| | |
|--------------------------------------|---|
| Warranty | 5 Year Warranty - For more information go to www.saturnled.eu/warranty |
| Marks & Symbols | CE -- SELV -- RoHS -- EMC -- WEEE |
| Quality Assurance System | SaturnLED quality assurance to ISO9001:2008 |
| Certificate of Conformity | Available on request - technical@saturnled.eu |
| Manufactured in Accordance to | British Standard - BS EN 60598 - 2 - 1 |

Datasheet generated from <http://www.electrika.com> last updated Wednesday, February 21, 2018 10:32:11 AM