

EASI6001

Easitrade 12W 4000K IP20 LED Slimline Circular Emergency Downlight



General Details

| | |
|--------------------|---|
| Finish | Matt White |
| Product Weight | 0.65kg |
| Overall Dimensions | A 165mm X B 11.5mm - Cutout 145mm |
| Bar Coding | Saturn LED coding in accordance with EAN-12 & ITF-14 |
| IP Rating | IP20 |
| Energy Rating | A* - (Very Low Energy) |
| Emergency | 3 hour - see www.saturnled.eu/warranty for more info |

Light Source

| | |
|--------------------------|-----------------------|
| Wattage & Lumens | 12W - 960LM - 80 lm/W |
| Colour Temperature | 4000K |
| CRI Ra | Ra > 80 |
| Lifespan | 30,000 Hours |
| Lamp Working Temperature | <50°C |
| Beam Angle | 110° |



Electrical

| | |
|---------|--------------------------|
| Voltage | 220-240V. 50 / 60Hz. AC. |
|---------|--------------------------|

| | |
|---------------------|------|
| Running Current (I) | 0.1A |
|---------------------|------|

| | |
|---------------------------|-----|
| Total Running Wattage (W) | 12W |
|---------------------------|-----|

| | |
|---------------------------|----------|
| Electrical Classification | Class II |
|---------------------------|----------|

| | |
|-------------------------------|-----|
| Power Factor Correction (PFC) | 0.9 |
|-------------------------------|-----|

| | |
|--------------------------------|-----------------------------|
| Cabling Electrical Connections | Screw fix in terminal block |
|--------------------------------|-----------------------------|

| | |
|------------|----------|
| LED Driver | Tridonic |
|------------|----------|

Installation

| | |
|---------------|--|
| Method of Fix | Recessed into a standard ceiling or ceiling tile |
|---------------|--|

| | |
|---------------------------------|---|
| Recommended Working Temperature | Minimum Temp -10°C to Maximum Temp + 40°C |
|---------------------------------|---|

| | |
|-------------------|-----------------------|
| Instruction Sheet | Supplied with product |
|-------------------|-----------------------|

Origin & Markets

| | |
|------------------------|---|
| Country of Manufacture | Designed & tested in Europe - Manufactured in China |
|------------------------|---|

| | |
|-----------------|---|
| Intended Market | Europe, Middle East & Australia 220 - 240Volt |
|-----------------|---|

Materials

| | |
|-----------------------|--|
| Main Housing Material | Polycarbonate Trim & Diffuser, Die-cast aluminium Body |
|-----------------------|--|

| | |
|----------------------|-----------------------|
| Fixings Main Housing | Spring Clips Provided |
|----------------------|-----------------------|

| | |
|--------------|------------------------------|
| Front Shield | Clear Polycarbonate Diffuser |
|--------------|------------------------------|

Approvals

| | |
|----------|---|
| Warranty | 3 Year Warranty - For more information go to www.saturnled.eu/warranty |
|----------|---|

| | |
|-----------------|-----------------------------------|
| Marks & Symbols | CE -- SELV -- RoHS -- EMC -- WEEE |
|-----------------|-----------------------------------|

| | |
|--------------------------|---|
| Quality Assurance System | SaturnLED quality assurance to ISO9001:2008 |
|--------------------------|---|

| | |
|-------------------------------|--|
| Manufactured in Accordance to | British Standard - BS EN 60598 - 2 - 1 |
|-------------------------------|--|

